pneumatic connection





# It is a hundred percent Oil-Free system.

**THROUGH** QUALITY

#### **OXYMAK Innovative Gas Systems**

Generator Model :ISO 10 FT CONTAINER	Product Code MO-20
Desing pressure	1 bar

Operating pressure 1 bar

Net weight 3300 kg

Noise level 60 dB (A) Oxygen pressure 5 bar

Ambient temperature +5 to +40 °C

Electrical connection 230V50Hz+/-%10 Power consumption 1320 W

Temperature 20 °C

Above Sea Level 0 m

Pressure 1.0133 bar Humidity 70 %

Dimension 2591x2438x2291 (mm)

Oxygen Purity	90%	93%	94%	95%	
Capacity (Nm3/h)	31.2	29	28	28	
Compressed air (Nm3/h)	288	288	288	288	Oil Free Compressor
Product vessel (I)					No Product Tank is needed
Compressed air vessel (I)					No Product Tank is needed
Compressed air inlet					nneumatic connection

#### **Generator Specification**

Connection O2 output

- Basic module in portable mounting frame with sealed enclosure
- Front control panel with main switch, operating time counter, oxygen sensor, pressure gauge
- With air inlet filter (99.999%)
- Compressed air piston compressor (Oil Free)
- Radial fan
- Oxygen booster (Oil free)
- Working stop function in the desired pressure range
- Temperature alarm monitor (protection against overheating)
- Oxygen PSA module (for continuous operation)

# **Compressed air specification**

free of all contamination, 100% Breathable air compressor

# OXYMAK

# **Touch Control Panel**

Standard	Option
Oxygen analyzer	Flow meter
7"Color Touch Monitör	
Remote access	

#### **Material**

External protection Powder oven paint, Pneumatic Piping, Specially designed components suitable for medical use, High quality Touch Screen Control Unit, Plug and play installation, Low energy consumption,