



Generator Model	Product Code O-20
Desing pressure	11 bar
Operating pressure	7 bar
Net weight	160 kg
Noise level	55 max 85 dB (A)
Ambient temperature	+5 to +40 °C
Electrical connection	220V 50-60 Hz 220V 50Hz
Power consumption	150 W
Safety class	54 IP
Temperature	20 °C
Above Sea Level	0 m
Pressure	1. 0133 bar
Humidity	70 %
Inlet Filtration	0.01 micron
Inlet Filtration * (ACfilter)	0.003 micron
Outlet Filtration	3 bis 5 micron
Dimension	740x800x1800 LxWxH (mm)

Oxygen Purity	90%	93%	94%	95%	99%
Capacity (Nm3/h)	1,6	1,4	1,3	1,3	Optional
Compressed air factor	11	11	11	11	Optional
Compressed air (Nm3/h)	17,60	15,4	14,3	14,3	Optional
Compressed air (m3/h)	18,9	16,5	15,3	15,3	Optional
Product vessel (l)	90	90	90	90	Optional
Compressed air vessel (l)	150	150	150	150	Optional
Compressed air inlet	½"	½"	½"	½"	½"
Connection O2 output	½"	½"	½"	½"	½"

Generator Specification

PSA Oxygen Generators separate oxygen from pressurised air.

The composition of the product is determined by measuring the residual oxygen content.

The oxygen content is calculated by subtracting the residual oxygen content from 100 %.

Air is composed of nitrogen (78.1%), oxygen (20.9 %), Argon (0.9 %), CO2 (0.03 %), and some inert gases

Compressed air specification

Dew point +3 °C, Air quality:according to ISO 8573.1, class 1 solid particulates and oil class 4 humidity,

free of all contamination (free of ozone)

Touch Control Panel

Standard	Option
4" Colorless	7" Color Touch Monitor
Inlet Filters 0.01 micron	Inlet temperature
Outlet filter 5-3 micron	Inlet dew point
4 different languages	Outlet dew point
Operational status	Flow meter
Outlet flow regulator	Outlet pressure
Inlet-Outlet pressure regulator	Oxygen analyzer

Material

Outside protection,Piping,Valves,powder paint coated

stainless steel or galvanized steel,stainless steel AISI 316 LPA actuator